

STANDARD :-

EN388:2016



4X43CX



CAT II



INDUSTRY

Glass cutting

Sheet metal Handling

Sharp small parts Handling

Part assembling

General Duty

DESCRIPTION

The Nitrile sandy finish provide excellent grip protect the hands, against water and oily environment

Great abrasion resistance fully dipped nitrile sandy provides liquid repellence and enhanced grip in water and oily environment

Ergonomic design keep hand smart and great comfort which improve the working efficiency

Anti-cut, anti-slip excellent abrasion

FEATURES/BENEFITS

Level 5 cut resistance

Unique double dipped provides superior grip under dry wet condition

Resistant to abrasions, punctures, oil, and chemicals

Fully coating offers excellence resistance to liquids provide superior grip in wet and oily environment



LINER MATERIAL

HPPE, Spandex, Nylon, Glass fiber

PALM COLOUR

Black / Black

GAUGE

13G

PALM COATING

Nitrile fully coated Sandy finish

CUFF

Elasticized Knit

SIZE

M/L/XL

DIMENSIONS

9 x 5.25 in

SAFEKEEPING

Protect from Exposure to ultraviolet (UV) light

Keep Store Area clean and Dry

Avoid Store near high Temperatures areas

ADDRESS

Head office: A-7, Deendayal Market,
Powerhouse Road, korba, (C.G) Pin Code - 495677

E- mail : sales@glovex.in / cg@glovex.in / od@glovex.in
Website : www.glovex.in

Tel : +91 9981155510