

STANDARD :-

EN388:2016



3142XX



CAT II



Crinkled Finish

INDUSTRY

Automotive Industry

Transportation

Warehousing

Agriculture

Building & Construction

DESCRIPTION

High cost-effective choice of general- purpose work

The Crinkle latex finish provide the excellent grip in fry and wet condition

Good dexterity and flexibility in medium heavy duty works

Good tear and puncture resistance

FEATURES/BENEFITS

Different coating latex gloves to suit various work condition and application

Latex Gloves have a high abrasion and tear resistance due to its denser construction

Latex Gloves were created for a broad range of general working application such as handling and caring in dry and wet condition

colour variant available

LINER MATERIAL

Polyester

GAUGE

13G

PALM COLOUR

Brown / Black

PALM COATING

Latex Crinkle

CUFF

Elasticized Knit

SIZE

M/L/XL

DIMENSION

9 x 5.25 in.

SAFEKEEPING

Protect from Exposure to ultraviolet (UV) light

Keep Store Area clean and Dry

Avoid Store near high Temperatures areas

ADDRESS

Head office: A-7, Deendayal Market,
Powerhouse Road, korba, (C.G) Pin Code - 495677

E- mail : sales@glovex.in / cg@glovex.in / od@glovex.in
Website : www.glovex.in

Tel : +91 9981155510