

STANDARD :-

EN388:2016



4X42DX



CAT II



INDUSTRY

Glass & Steel Industry

Maintenance

Automobile Industry

Mechanical Assembly

Construction

LINER MATERIAL

HPPE, Spandex, Nylon, Glass fiber

DESCRIPTION

High level cut performance EN ISO level 5

Nitrile smooth coating provide excellent grip performance dry and wet working condition

Breathable liner allow to high cut level comfort and dexterity

Excellent abrasion performance and durability

FEATURES/BENEFITS

HPPE, Spandex, Nylon, Glass fiber liner for high cut resistance and lightweight comfort

Nitrile Coating for a strong grip

Durable and Resistant to abrasion Tear and Punctures

PALM COLOUR

Grey / Black

GAUGE

13G

PALM COATING

Nitrile Smooth

CUFF STYLE

Elasticized Knitted

SIZE

M/L/XL

DIMENSIONS

9 x 5.25 in.

SAFEKEEPING

Protect from Exposure to ultraviolet (UV) light

Keep Store Area clean and Dry

Avoid Store near high Temperatures areas

ADDRESS

Head office: A-7, Deendayal Market,
Powerhouse Road, korba, (C.G) Pin Code - 495677

E- mail : sales@glovex.in / cg@glovex.in / od@glovex.in
Website : www.glovex.in

Tel : +91 9981155510