

STANDARD :-

EN388:2016



(4X43DX)



CAT II

**INDUSTRY**

Glass Industry

Steel Industry

Automotive Industry

Wood Industry

Construction

Petroleum Industry

LINER MATERIAL

HPPE, Spandex, Nylon, Glass Fiber

DESCRIPTION

High Level of cut performance EN IOS level D

Nitrile Sandy finish coating provide excellent grip performance in grease and oil working condition

Breathable, high cut level D, comfort and dexterity

Excellent, abrasion performance and durability

FEATURES/BENEFITS

HPPE, Spandex, Nylon, Glass fiber liner for high cut resistance and comfort

Nitrile Sandy Finish coating for a strong grip in wet and oily conditions

Durable and resistant to abrasion and punchers

Flexible and breathable for extended wear

**PALM COLOUR**

Black / Black

GAUGE

13G

PALM COATING

Nitrile Sandy Finish

CUFF STYLE

Knit Wrist

HSN CODE

61161000

CUFF

Elasticized Knit

SIZE

M/L/XL

DIMENSION

9 x 5.25 in.

SAFEKEEPING

Protect from Exposure to ultraviolet (UV) light

Keep Store Area clean and Dry

Avoid Store near high Temperatures areas

ADDRESS

Head office: A-7, Deendayal Market,
Powerhouse Road, korba, (C.G) Pin Code - 495677

E- mail : sales@glovex.in / cg@glovex.in / od@glovex.in
Website : www.glovex.in

Tel : +91 9981155510