

STANDARD :-

EN388:2016



4X42FX



CAT II



INDUSTRY

Glass and Steel Industry

Automotive Industry

Construction

Maintenance

Logistics

DESCRIPTION

Adamas® fiber liner offers the high resistance performance in ISO Cut F / ANSI Cut A6 level

Breathable PU smooth coated and lightweight liner allow high level comfort and dexterity, keep hand cool and dry

Great grip performance in dry working condition

Excellent abrasion performance and durability in use

FEATURES/BENEFITS

420% higher cut index compared with standard HPPE new generation cut resistance

Alternative Knitting option 13G, 15G, 18G, 21G between A3-A9 solution

Adamas® Fiber Liner, Nylon, spandex

Allergy free, Steel free, glass Fiber free and Skin Friendly

LINER MATERIAL

Adamas

GAUGE

13G

PALM COLOUR

Grey / Grey

PALM COATING

Polyurethane (PU) Smooth

CUFF

Elasticized Knit

SIZE

M/L/XL

DIMENSIONS

9 x 5.25 in

SAFEKEEPING

Protect from Exposure to ultraviolet (UV) light

Keep Store Area clean and Dry

Avoid Store near high Temperatures areas

ADDRESS

Head office: A-7, Deendayal Market,
Powerhouse Road, korba, (C.G) Pin Code - 495677

E- mail : sales@glovex.in / cg@glovex.in / od@glovex.in
Website : www.glovex.in

Tel : +91 9981155510